


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	RELEASED TO PRODUCTION	04/16/2025	REP

- STANDARD NOTES:
- BREAK ALL SHARP CORNERS AND EDGES.
 - RACEWAY INDUCTION HARDENING CASE DEPTH TO BE NO LESS THAN .118 INCHES AT HRC 55-62.
 - GREASE TO BE STANDARD EP2.
 - SOFT SPOT TO BE MARKED WITH AN "S" ON INNER AND OUTER RING NON-MOUNTING SURFACE INDICATING RACEWAY HARDNESS GAP.
 - CENTERLINE OF GREASE FITTING, 1X EQUALLY SPACED, 1/8-27 NPT FITTINGS, PROTRUSION FROM OD (OUTER RING) NOT TO BE GREATER THAN .75.
 - PERMANENTLY MARK INFO, .06 MIN FONT HEIGHT.

MARKING TO INCLUDE:
PART NUMBER
SERIES NUMBER IN LOT
DAY-MONTH-YEAR

EXAMPLE:
30P.0080.06.001
001 (002, 003, ETC)
25-11-2014

7. WEIGHT: 2 lbmass

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF POTESTA & COMPANY LLC. AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT POTESTA & COMPANY'S WRITTEN AUTHORIZATION.			
DRAWN GVS	4/16/2025	ALL DIMENSIONS: in.	
CHECKED			1239 Hudson Gate Dr. Hudson, OH 44236 PH: 330.633.7735 www.SlewPro.com
QA			
MFG			
APPROVED			
SIZE D	SHEET 1 OF 1	SCALE NOT TO SCALE	PART NO. 30P.0080.06.001
TITLE		BEARING ASSY, PLAIN, FOUR POINT, SINGLE ROW BALL	