


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	RELEASED TO PRODUCTION	10/12/2023	REP

- STANDARD NOTES:
- BREAK ALL SHARP CORNERS AND EDGES.
 - RACEWAY INDUCTION HARDENING CASE DEPTH TO BE NO LESS THAN .079 INCHES AT HRC 50-60.
 - GREASE TO BE STANDARD EP2.
 - SOFT SPOT TO BE MARKED WITH "S".
 - CENTERLINE OF GREASE FITTINGS, 1X EQUALLY SPACED, 1/8-27 NPT, FITTING PROTRUSION FROM ID (INNER RING) NOT TO BE GREATER THAN .75.
 - STAMP "G" ON TOP OF OUTER RACE INDICATING RACEWAY HARDNESS GAP.
 - PERMANENTLY MARK INFO, .06 MIN FONT HEIGHT.
- MARKING TO INCLUDE:
PART NUMBER
SERIES NUMBER IN LOT
DAY-MONTH-YEAR
- EXAMPLE:
30P.0290.19.002
001 (002, 003, ETC)
25-11-2014
8. WEIGHT: 40 lbmass

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF POTESTA & COMPANY LLC. AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT POTESTA & COMPANY'S WRITTEN AUTHORIZATION.

DRAWN Gregg VanSuch	10/12/2023	ALL DIMENSIONS: in.	
CHECKED			1239 Hudson Gate Dr. Hudson, OH 44236 PH: 330.633.7735 www.SlewPro.com
QA			
MFG			
APPROVED			
SIZE D	SHEET 1 OF 1	SCALE NOT TO SCALE	TITLE BEARING ASSY, PLAIN, FOUR POINT, SINGLE ROW BALL
		PART NO.	30P.0290.19.002