


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	RELEASED TO PRODUCTION	10/12/2023	REP

- STANDARD NOTES:
- BREAK ALL SHARP CORNERS AND EDGES.
  - RACEWAY INDUCTION HARDENING CASE DEPTH TO BE NO LESS THAN .079 INCHES AT HRC 50-60.
  - GREASE TO BE STANDARD EP2.
  - SOFT SPOT TO BE MARKED WITH "S".
  - CENTERLINE OF GREASE FITTINGS, 1X EQUALLY SPACED, 1/8-27 NPT, FITTING PROTRUSION FROM ID (INNER RING) NOT TO BE GREATER THAN .75.
  - STAMP "G" ON TOP OF OUTER RACE INDICATING RACEWAY HARDNESS GAP.
  - PERMANENTLY MARK INFO, .06 MIN FONT HEIGHT.
- MARKING TO INCLUDE:
- PART NUMBER
  - SERIES NUMBER IN LOT
  - DAY-MONTH-YEAR
- EXAMPLE:
- 30P.0290.19.003  
001 (002, 003, ETC)  
25-11-2014
8. WEIGHT: 40 lbmass

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF POTESTA & COMPANY LLC. AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT POTESTA & COMPANY'S WRITTEN AUTHORIZATION.

DRAWN Gregg VanSuch	10/12/2023	ALL DIMENSIONS: in.	
CHECKED			1239 Hudson Gate Dr. Hudson, OH 44236 PH: 330.633.7735 www.SlewPro.com
QA			
MFG			
APPROVED			
SIZE D	SHEET 1 OF 1	SCALE NOT TO SCALE	PART NO. 30P.0290.19.003