


REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	RELEASED TO PRODUCTION	03/03/2023	REP

- STANDARD NOTES:
- BREAK ALL SHARP CORNERS AND EDGES.
  - RACEWAY INDUCTION HARDENING CASE DEPTH TO BE NO LESS THAN .118 INCHES AT HRC 56-62.
  - GREASE TO BE STANDARD EP1.
  - SOFT SPOT TO BE MARKED WITH "S".
  - CENTERLINE OF 2X GREASE HOLE, LOCATED AS SHOWN, 1/8-27 NPT FITTING, PROTRUSION FROM OUTER DIAMETER (OD) NOT TO BE GREATER THAN .75.
  - STAMP "G" ON TOP OF OUTER RACE INDICATING RACEWAY HARDNESS GAP.
  - PERMANENTLY MARK INFO, .06 MIN FONT HEIGHT.
- MARKING TO INCLUDE:  
PART NUMBER  
SERIES NUMBER IN LOT  
DAY-MONTH-YEAR
- EXAMPLE:  
30P.0508.25.002  
001 (002, 003, ETC)  
25-11-2014
8. WEIGHT: 143 lbmass

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF POTESTA & COMPANY LLC. AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT POTESTA & COMPANY'S WRITTEN AUTHORIZATION.

DRAWN Gregg VanSuch	3/3/2023	ALL DIMENSIONS: in.	
CHECKED			1239 Hudson Gate Dr. Hudson, OH 44236 PH: 330.633.7735 www.SlewPro.com
QA			
MFG			
APPROVED			
SIZE D	SHEET 1 OF 1	SCALE NOT TO SCALE	PART NO. 30P.0508.25.002